

over floor trunking



300 92



300 93



328 00




Conform to standard EN 50085-2-2

For creating a link between trunking, column, mini-column, floor units or protecting cables on passageways

Supplied with cover

Over floor trunking 50 x 12 mm

Pack	Cat.Nos	Trunking
54	300 92 ⁽¹⁾	Length 2 m, supplied with cover 3 compartments Capacity 1: max. Ø9 mm Capacity 2: max. Ø6 mm IP 40 - IK 07 RAL 7030




Accessories

10	300 12	Cover joint
10	300 11	Flat angle
4	300 13	Junction box

Over floor trunking 75 x 18 mm

Pack	Cat.Nos	Trunking
36	300 93 ⁽¹⁾	Length 2 m, supplied with cover 3 compartments Capacity 1: max. Ø14 mm Capacity 2: max. Ø11 mm IP 40 - IK 07 RAL 7030




Accessories

10	300 19	Cover joint
10	300 18	Flat angle
4	300 13	Junction box

Over floor trunking 92 x 20 mm

Pack	Cat.Nos	Trunking
20	328 00 ⁽¹⁾	Length 2 m, supplied with cover 4 compartments Equipped with 2 adhesive strips for better floor fixing Capacity 1: max. Ø14.5 mm Capacity 2: max. Ø9.5 mm IP 40 - IK 08 RAL 7016



Accessories

10	328 07	End cap
10	328 03	Cover joint
5	328 02	Flat angle
1	328 05	Connection for mini-trunking installed as 60 x 20 or 75 x 20 skirting trunking
5	328 01	Distribution box For spurs in 4 directions with separation of currents

Junction for trunkings

5	107 71 + 106 90	To be used with Cat.No 328 00 For cover 65 mm
5	107 72 + 106 90	For cover 85 mm