

# 19" XL VDI wall mounting cabinets and accessories






**Technical characteristics (p. 430)**

IP 20 - IK 08  
 Equipped with:  
 1 reversible curved door made of safety glass  
 2 lateral panels removable from inside (no tools needed)  
 Key locking 2433A  
 2 x 19" adjustable depth uprights  
 Top and bottom cable entry plates  
 Top and bottom grilles for natural ventilation, can take a fan in the top part  
 White RAL 9002

Pack	Cat.Nos	Fixed cabinets			
<b>400 mm depth cabinets</b>					
		Capacity	Width (mm)	Height (mm)	Permissible load (kg)
1	340 36	6 U	600	350	18
1	340 37	9 U	600	500	27
1	340 38	12 U	600	600	36
<b>580 mm depth cabinets</b>					
		Capacity	Width (mm)	Height (mm)	Permissible load (kg)
1	340 46	9 U	600	500	27
1	340 48	12 U	600	600	36
1	340 49	16 U	600	800	48

Pivoting cabinets					
600 mm depth cabinets					
Comprising:					
- A base (wall fixing)					
- A pivoting body providing unrestricted access to the rear of the cabinet for easy installation and maintenance					
Reversible pivoting direction					
Supplied with a horizontal cable support					
Cat.No 340 78					
		Capacity	Width (mm)	Height (mm)	Permissible load (kg)
1	340 51	9 U	600	500	27
1	340 52	12 U	600	600	36
1	340 53	16 U	600	800	48
1	340 55	21 U	600	1 000	63

Pack	Cat.Nos	Accessories
1	340 83	<b>Cable entry plate</b> Fits in place of the solid plate at top or bottom Plate with brush seal 
1	348 39	<b>Fans</b> Fix directly in the top of the cabinet 230 V~ fan with 2.5 m cord
1	348 45	12 V= fan with 2.5 m cord Reduced noise Fan speed depending on temperature Integrated thermostat Requires a 12 V= power supply unit Cat.No 047 95 (p. 144)
1	340 80	<b>Cable supports</b> Fix horizontally at the back of the cabinet for cable management
1	340 78	For fixed cabinets For pivoting cabinets 
1	332 25	<b>Fixed shelves</b> 1 U, depth 250 mm, for all fixed and pivoting cabinets Max. load 20 kg
1	332 28	1 U, depth 300 mm, for 580 and 600 mm cabinets Max. load 20 kg
1	331 36	<b>IP 2x DIN rail kit</b> For mounting Lexic Legrand equipment Fits directly onto 19" uprights Helps compliance with EMC requirements Comprises: • metal box • 24 module DIN rail • terminal block for grounding • 3 U faceplate • 24 module blanking plate • 14 cable entry glands
1	331 39	<b>Earthing kit</b> 3 x green-yellow wires Length 300 mm, 6 mm <sup>2</sup>



**Cable management**

**see p. 440-441**